1. (Currently Amended) A thrombus capture catheter comprising:

a sheath with a lumen passing therethrough from a proximal end thereof to a distal

end thereof and being closed at the proximal end thereof by a closing member;

a flexible shaft having a proximal end and a distal end, said flexible shaft being a wire

member that serves as a guide wire for a balloon catheter and being removably arranged in

the lumen of said sheath; and

a thrombus capture member having a proximal end and a distal end and being

provided on a distal portion of said shaft;

said thrombus capture member comprising a crossed wire member and a filter

attached thereto, said crossed wire member comprising a plurality of spirally-configured

wires including right-handed spiral wires and left-handed spiral wires.

one of said right handed spiral wires or left-handed spiral wires being arranged

spirally around said shaft to surround the shaft,

while the other of said right-handed spiral wires or left handed spiral wires being

arranged spirally above the one of said either right-handed spiral wires or left handed spiral

wires so that said right-handed spiral wires and left-handed spiral wires to which cross each

other, thereby forming an original configuration swollen in middle portion and tapered to the

proximal and distal ends thereof under a normal condition,

said filter being provided with pores and being mounted on the distal side of said

crossed wire member to cover a part of the swollen portion thereof, said crossed wire

JMS/CTT/ktp

Application No. 10/642,591

Amendment dated June 15, 2009

Reply to Office Action of March 16, 2009

Docket No.: 0020-5166P

Art Unit: 3731 Page 5 of 15

member being fixed at the proximal end thereof to said shaft and being slidably mounted at

the distal end on said shaft, said shaft passing through the thrombus capture member and

protruding from the distal end of the thrombus capture member,

said thrombus capture member being removably held in said sheath in a contracted

condition being restorable to said original configuration thereof when protruded from said

sheath through the distal end thereof by pulling said sheath in the direction of the proximal

end of the sheath.

2. (Cancelled)

3. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

pores of said filter have a diameter ranging from 50 to 1000 micrometers.

4. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

said closing member is a tubular member having a closed proximal end and an open distal

end into which said sheath is inserted, said closing member is provided on a central axis

thereof with a through-hole passing through said closed proximal end thereof for insertion of

said shaft and includes a hemostatic valve arranged close to the through-hole, and wherein

the proximal portion of said shaft is protruded from the sheath through said through hole and

hemostatic valve.

5. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

said sheath is provided in a side wall close to the distal end thereof with a side hole allowing

JMS/CTT/ktp

Application No. 10/642,591

Amendment dated June 15, 2009

Reply to Office Action of March 16, 2009

Docket No.: 0020-5166P

Art Unit: 3731 Page 6 of 15

the shaft to pass therethrough, and with a second lumen communicated with said proximal

side wall and allowing said thrombus capture member to pass through, a part of said shaft

extending beyond a proximal side of said thrombus capture member being protruded from

the sheath through said side hole.

6. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

said closing member is provided with a side infusion tube.

7. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

said thrombus capture member is further provided at the distal end thereof with a slide ring

assembly comprising an inner ring and an outer ring, the wires of said crossed wire member

being sandwiched between and fixed to said inner and outer rings at the distal end of said

thrombus capture member, said inner ring being slidably mounted on the shaft to allow said

thrombus capture member to be moved along the shaft.

8. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

said thrombus capture member is slidably attached at the distal end thereof to the shaft by a

slide ring and fixed at the proximal end thereof to the shaft by a fixed ring.

9. (Previously Presented) The thrombus capture catheter according to claim 1, wherein

the thrombus capture catheter according to claim 1, wherein said filter is a funnel-shaped

member including a cylindrical part, a constringent part and a constricted part extending

from the smaller end of the constringent part, said constringent part being provided whith

JMS/CTT/ktp

Application No. 10/642,591 Amendment dated June 15, 2009 Reply to Office Action of March 16, 2009 Docket No.: 0020-5166P Art Unit: 3731 Page 7 of 15

plural pores which prevents the thrombus from passing therethrough to capture the thrombi in the filter while allowing the body fluid to pass therethrough.